

	PERMA Battery Co., Ltd.	VER:A
	TEL: 0086-755-29020460 WEB: www.permabattery.com	DATE: 02/02/2015

Non-Rechargeable Lithium Battery Specification

Model: ER14505

Primary Lithium Battery

ER14505 3.6V 2.7Ah

3.6V Primary lithium-thionyl chloride
(Li-SOCl₂) Energy Type

For low drain/long term operating applications requesting superior voltage response in -55°C ~+85°C environments

Cell size references

UM3-R6-AA

Alternative models LS14500/LST14500/LS14500G/TL4903/TL5903/SB-AA01

Electrical characteristics

(Typical values relative to cells stored for one year or less at +30°C max.)

Nominal capacity 2.7Ah

(At 1mA +20°C, 2.0V cut off. The capacity restored varies according to current, temperature, cut off)

Open circuit voltage (At 20°C) 3.66V

Nominal voltage (At 1mA +20°C) 3.6V

Max. continuous current (at +20°C) 100mA

Typical Max. Pulse current (at +20°C) 200mA

Pulse capability: Typically up to 200mA (200mA/0.1second pulses drained every 2min at 20°C from cells with 20µA base current, yielding voltage readings above 3.0V. The readings may vary according to pulse characteristics, temperature and cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions.

Storage (recommended) +30°C Max

Operating temperature range
(High and low temperature will lower the capacity and load voltage.) -55°C ~+85°C

Physical characteristics

Diameter(Max) 14.5mm(0.55in)

Height(Max) 50.5mm(2in)

Typical weight 17g(0.557oz)

Available terminal suffix radial tabs, radial pins, axial leads, flying leads



PERMA Battery Co., Ltd.

VER:A

TEL: 0086-755-29020460
WEB: www.permabattery.com

DATE:
02/02/2015

ER14505



Key features

- >High and stable load voltage
- >Superior drain capacity
- >Low self-discharge rate (less than 1% after 1 year of storage at 20°C)
- >Stainless steel container
- >Hermetic glass-to-metal sealing
- >Laser welding
- >Non-flammable electrolyte

Main applications

- >Radiocommunication and other military applications
- >Alarms and security systems
- >Beacons and emergency location transmitters
- >GPS equipment
- >Metering systems
- >Led lighting applications
- >Others

Storage

- >Cells should be stored in a clean & dry (less than 30% RH) area
- >Temp. should not exceed +30°C

Warning

- >Do not use if cell casing is mangled
- >Do not use different model of cell in series
- >Soldering the tag should be finished in few seconds
- >Do not try to recharge

